

Name : Multi-functional Flow Control Valve

Model : TMF74A

Size :

Product introduction :



Product Description:	Multi-functional Flow Control Valve (Automatic Softener Valve)
Model No.:	TM.F74A
Material:	ABS reinforced
Product Origin:	China
Brand Name:	RUNXIN
Price Terms:	FOB Shanghai / Ningbo
Payment Terms:	T/T 100% in advance
Chinese Patent No.:	ZL02220153.X ZL200420078956.5
Certification:	CE, ROHS
International Pat. No.	WO 2006/OO7772

Features:

- 1) It adopts the seal slice, scuff resistance, corrosion proof for opening and closing. Mechanical part is more reliable.
- 2) Keyboard locked function: If the keyboard has not been operated within one minute, it will be locked by itself to avoid incorrect operation.
- 3) LED colorful screen: The colorful screen will continuously show it is in normal service state. If the power has been cut over 3 days, the clock figure will flicker continuously to remind to reset the current time, but other parameters are kept.

- 4) No water flows out while single tank type control valve regeneration.
- 5) One valve has two kinds of running time counting: by day or by hour. By dialing a switch remarking ON and 1 on PC board to exchange. After exchange, please restart the power.
- 6) Have output signal connector: There are three output signal connectors on PC board: N/O, N/C. COM which could be connected with booster pump and solenoid valve.
- 7) Have interlock function.

Technical Parameter:

1) Control Mode: Automatic/Time Type/Down-flow Reg.
2) Suited Pressure: 0.15~0.6MPa
3) Suited Water Temperature: 5--45°C
4) Transformer Input: 100-240V/50-60Hz
5)Maximal Water Treatment Capacity: 10 m ³ /h
6) Tank Diameter for matching: 10"- 30"
7) Water Inlet/Outlet: 2"M (Male Thread)
8) Drain Outlet: 1"M (Male Thread)
9) Brine Line Connector: 1/2"M (Male Thread)
10) Riser Pipe: 1-1/2 "D-GB (50mm)
11) Base (Tank thread): 4"-8UN

Range of Application:

Household purification, softening system	Boiler softening water system
RO pre-treatment system	Swimming pool filters equipment
Ion exchange equipment	

Packing: 4SETS / CTN

Carton Dimension: 798*568*305(MM)

Product Accessories packed with valve:

Accessory Description	Qty	Accessory Description	Qty
4" Base Seal Ring (Φ104.6×Φ5.7)	1PC	1/2"Brine Tube Hose Connector	1PC
Drain Line Flow Control(5#,6# injector no washer)	1PC	Tube Bushing	1PC
Transformer (EU plug, US plug or UK plug)	1PC		



DX GROUP

CÔNG TY CỔ PHẦN BẮT ĐỘNG SẢN VÀ MÔI TRƯỜNG

DÂN XUÂN

496-498 Đường 3 Tháng 2, F.14, Q.10, TP. Hồ Chí Minh

Tel: (08) 38644756 – 38659321 – 38655505 Fax: (08) 8649249